



Falkenoil Antifreeze GW 12 (-40°)

Description/Application/Properties

Falkenoil Antifreeze GW 12 (-40°) is a ready water-diluted antifreeze based on ethylenglycole, to be used for all motor vehicles, which require silicate-free products (e.g. Ford, GM and MAN). It contains at least 60% antifreeze concentrate and is applicable for all established engines inclusive the modern high performance aluminium-motors. It is compatible with all coolant brands(also VW G 11).coolant brands (also VW G 11).

- may be used a life time through for grey iron - and alu motors
- protects all metallic materials in the system
- is eco-friendly, because it is free of nitrites, amines, phophates and silicates
- provides all-seasons protection of the cooling system

Specification/Recommendation

VW/Audi/Seat/Skoda TL744-D/F (G12/12+)
John Deere JDM H5
Opel-GM GMW 3420
Renault-Nissan 41-01-001/-S Type D
Caterpillar A4.05.09.01
Cummins IS series u N14
Komatsu 07.892 (2009)
Deutz/MWM 0199-99-2091/8
Volvo 014 GS 17009

MB 325.3
MAN 324 SNF
MTU MTL 504B
Jenbacher TA 1000-0201
Fiat MAT3624
Mazda MEZ MN 121 D
Liebherr MD1-36-130
Ford WSS-M97B44-D

Falkenoil Antifreeze GW 12 (-40°)	unit	value
Density at 20°C	kg/m ³	1076
Colour		Violet
Flash Point	°C	>100
pH (35%)		8,6
Boiling Point	°C	>100
Pour Point	°C	-40