



Falkenoil Antifreeze GW 12 (Concentrate)

Description/Application/Properties

Falkenoil Antifreeze GW 12 (Concentrate) is a antifreeze based on ethylenglycole, to be used for all motor vehicles, which require silicate-free products (e.g. Ford, GM and MAN). It is applicable for all established engines inclusive the modern high performance aluminium-motors. It is compatible with all coolant brands (also VW G 11).

Falkenoil Antifreeze GW 12 (Concentrate)

- may be used a life time through for grey iron - and alu motors
- protects all metallic materials in the system
- is eco friendly, because it is free of nitrites, amines, phosphates and silicates
- provides all-seasons protection of the cooling system

Specification/Recommendation

VW/Audi/Seat/Skoda TL774-D/F (G12/12+)	MB 325.3	ADE
Bergen Engines 2.13.01	DAF 74002	Aston Martin
Case New Holland MAT3624	Detroit DFS93K217	Behr
Caterpillar A4.05.09.01	Deutz DQC CB-14	Chevrolet
Cummins CES 14603/CES 14439	Fiat MAT3624	Claas
Cummins IS series u N14	Ford WSS-M97B44-D	Fendt
Deutz/MWM 0199-99-2091/8	Foton Q-FPT 2313005-2013	Great Wall
Jaguar STJLR 651.5003	Jaguar CMR 8229	Hitachi
John Deere JDM H5	Jenbacher TA 1000-0201	Isuzu
Komatsu 07.892 (2009)	Liebherr MD1-36-130	Karosa
Land-Rover STJLR 651.5003	MAK A4.05.09.01	Kobelco
Leyland Trucks DW03245403	MAN 324 SNF	Proton
Mack 014 GS 17009	MAN B&W AG D36 5600	Rover
Opel-GM GMW 3420	Mazda MEZ MN 121 D	Santana Motors
Renault Trucks 41-01-001/-S Type D	Mitsubishi MHI	Saturn
SACM Diesel DLP799861	MTU MTL 5048	Semt Pielstick
Vauxhall GM 6277M (+B040 1065)	Saab B 040 1065	Tedom
Vauxhall GME L1301	Skoda 61-0-0257	Thermo King
Volvo 014 GS 17009	Wärtsilä 32-9011	Valtra
Volvo Penta/Trucks/Construction	Waukesha	Yanmar
ASTM D3306	NFR 15-601	E/L-1415b (MIL-Italy)
ASTM D4656	FVV Heft R443 (Germany)	FSD 8704 (MIL-Sweden)
ASTM D4985	JASO M325	NATO S-759
ASTM D6210	KSM 2142	Önorm V5123
BR 637	BT-PS-606 A (MIL-Belgium)	SAE J1034
BS 6580	DCSEA 615/C (MIL-France)	UNE 26-361-88/1

Falkenoil Antifreeze GW 12 (Concentrate)	unit	value
Density at 20°C	kg/m ³	1112
Colour		Violett
Flash Point	°C	>100
pH (35%)		8,3
Boiling Point	°C	>170