



## Falken oil Passenger Car Plus 10W-40

### Description/Application/Properties

**Falken oil Passenger Car Plus 10W-40** is a high performance low friction oil to be used in passenger cars gasoline and diesel engines. It is produced by blending high quality synthetic oils and mineral base stocks and additives of most progressive technology. Suitable also under severe operating conditions in modern passenger car engines, turbo- or non-turbo charged, and for vans, too.

**Falken oil Passenger Car Plus 10W-40** by its optimized formulation provides lowered fuel- and oil consumption. Because of its extended viscosity range the all seasons use is possible. A special booster raises the quality level up to API SN, which provides improved oxidation resistance, improved deposit protection, better wear protection, and better low-temperature performance over the life of the oil. This leads to an improved motor cleanliness and at least to an extended motor life.

### Specification/Recommendation

ACEA A3/B4                      MB 229.3  
API SN                              VW 502 00 / 505 00  
Renault RN 0700                PSA B71 2296

Falken oil Passenger Car Plus 10W-40	unit	value	method
Density at 15°C	kg/m <sup>3</sup>	860	DIN 51 757
Viscosity at 40°C	mm <sup>2</sup> /s	93,3	DIN 51 562
Viscosity at 100°C	mm <sup>2</sup> /s	14,6	DIN 51 562
Viscosity index		163	DIN ISO 2909
Pourpoint	°C	-42	DIN ISO 3016
Flashpoint	°C	232	DIN ISO 2592
TBN	mg KOH/g	10,6	DIN ISO 3771