



Falkenoil ATF MultiTech

Description/Application/Properties

Automatic Transmission Fluid which is made by multi-vehicle anti-shudder additive technology optimized for passenger car applications, used in an extensive range of European and American passenger car service fill applications, it also can be used in commercial vehicle applications and power steering.

- Exceptional oxidation behavior
- Anti-shudder durability
- smoother shifts over a long period of time
- excellent anti-rust properties

Specification/Recommendation

GM DEXRON II / II-D / II-E / III-G / III-H	GM/GMC/Opel/Saturn P/N 21005966 (transaxle)
Allison C-4, TES-295, TES-389	GM/GMC/Opel/Saturn P/N 22717466
BMW/Mini P/N 81 22 9 400 272/275	GM/GMC/Opel/Saturn P/N 88900925/9986195
BMW/Mini P/N 81 22 9 407 858/859	GM/GMC/Opel/Saturn T-IV, Type A Suffix A
BMW/Mini P/N 83 22 0 024 249/359	Jaguar JLM 20238 / 20292 / 21044 / K17
BMW/Mini P/N 83 22 0 026 922 (BMW 7045 E)	Jaguar WSS-M2C922-A1
BMW/Mini P/N 83 22 0 402 413	Aisin Warner JWS 3309
BMW/Mini P/N 83 22 0 403 248/249	Land Rover Texaco ETL-7045E
BMW/Mini P/N 83 22 7 542 290	MAN 339 A
BMW/Mini P/N 83 22 9 407 765 (BMW LA 2634)	Mercon V
Chrysler/Dodge/Jeep ATF+2/ATF+3/ATF+4	Mobil ATF 3309
Chrysler/Dodge/Jeep AS68RC ATF	Porsche P/N 000 043 204 41
Chrysler/Dodge/Jeep SP-III	Porsche P/N 000 043 205 09
Daimler/Mercedes MB 236.5, 236.6, 236.7	Porsche P/N 999 917 547 00 (A2)
Daimler/Mercedes MB 236.8, 236.9, 236.10, 236.91	PSA Peugeot Citroen P/N Z 000169756
FORD WSS-M2C919-E (Mercon V)	Renault Matic D2
FORD/Lincoln/Mercury P/N XT-2-QDX [M]	Renk Genuine Oil
FORD/Lincoln/Mercury P/N XT-2-QSM [Syn]	Saab 3309 - T-IV
FORD/Lincoln/Mercury P/N XT-5-QM or -DM [V]	Shell 3403-M115, LA 2634
FORD/Lincoln/Mercury P/N XT-8-QAW [Premium]	Texaco ETL 7045E / 8072B, N402
FORD/Lincoln/Mercury P/N XT-9-QMM5 [FNR5]	Voith H55.6335.XX
FORD/Lincoln/Mercury WSS-M2C922-A1	Voith Svc Bltn # 013 / 118
GM/GMC/Opel/Saturn P/N 19 40 700/767	Volvo P/N 1161521
VW/Audi G 052 025 A2, G 052 055	Volvo P/N 1161540 / 1161640
VW/Audi G 052 162 (A1, A2)	Volvo P/N 1273,41
VW/Audi G 052 990 (A2), G 055 025 (A2)	ZF TE-ML 11A / 11B
VW/Audi US 000 162	

Falkenoil ATF MultiTech	unit	value	method
Density at 15°C	kg/m ³	848	DIN 51 757
Viscosity at 40°C	mm ² /s	38,2	DIN 51 562
Viscosity at 100°C	mm ² /s	7,0	DIN 51 562
Viscosity index		150	DIN ISO 2909
Pourpoint	°C	-45	DIN ISO 3016
Flashpoint	°C	228	DIN ISO 2592